



BLANCO COOK Cooking System

BLANCO COOK extraction technology

COOK Frontcooking Station	138
Accessories for Frontcooking Station	140

BLANCO COOK table-top units

Induction hob	143
Induction wok	143
Deep griddle	144
Griddles	144
Ceran® hob	145
Pasta cooker	145
Deep fryer	146
Bain-marie	146
Hot plate	146
Accessories for table-top units	147

Front cooking system for professionals: BLANCO COOK with a licence to breathe freely.

The front cooking station is the heart of the mobile BLANCO COOK cooking system. With its highly efficient extraction and filter technology, it ensures an optimum climate and frees you from stationary extractor hoods. The front cooking station is available for two to four cooking units.

Thirteen different table-top cooking units enhance the front cooking station and allow flexible compositions.

With BLANCO COOK you can fry, cook, grill, deep-fry, keep hot and present – in an energy-saving, efficient and tempting way.



For good air
The three-sided air stream and an additional suction, route the rising cooking fumes directly into the extraction bridge, which means grease, moisture and bad odours don't have a chance.



**BLANCO COOK front cooking station:
well-designed down to the last detail.**

- The extraction bridge offers ample space for ingredients or serving, whilst affording a clear view of the preparation process.
- Functional design with one-piece flat surfaces.
- Socket outlets behind the cooking units ensure cables are stored safely.
- Fans and filters can be accessed from the cooking side.
- Usable storage space is located under the placement niche.

Faster, hotter, better! The BLANCO COOK front cooking system is on top form.

The next generation

Those who cook before their guests' eyes need to be able to trust their equipment unconditionally. BLANCO COOK offers innovative technology and reliable performance for professionals. In a high-quality BLANCO design for top performance with regard to handling and hygiene. With rotary knob control, you can adapt your energy consumption to the capacity level. Thanks to the compact design and a depth of just 62 cm, all table-top cooking units fit on all standard worktops and can be flexibly combined.



Induction hobs and induction woks

Depending on requirements, we offer a 1-zone induction hob, 2-zone induction hob, surface induction or induction wok – powerful, durable and extremely fast.



Ceran® hob

with 2 independently adjustable cooking zones.

Hot plate

with large heat-retaining area.

Pasta cooker

for energy-saving cooking and steaming in pasta baskets or GN cooking inserts.

Bain-marie

for keeping food hot and presenting dishes in GN containers.

BC ME multi element

offers storage space for cooking utensils and ingredients, an additional work surface and help when arranging the food.





The front cooking trio for mouthwatering cooking shows:
induction wok, ribbed griddle and pasta cooker.



Deep fryer

with swivelling heating and unheated cold zone at the bottom of the basin.



Deep griddle

can be used flexibly for braising, grilling or cooking.



Griddles

ribbed or flat – the seamlessly welded-in griddle achieves a uniform temperature as desired. Excessive grease is collected in the large catch tray. With independently adjustable heating zones, the double-wide griddle offers efficiency at the touch of a button.



Extra large
griddle

BLANCO COOK cooking system:
Innovative technology that everyone can taste.

BLANCO COOK front cooking station

- For 2, 3 or 4 BLANCO COOK table-top units
- Narrow extraction bridge for ideal visibility
- Extremely effective filter system
- Electronic control with filter change indicator
- Large storage surface on the odour filter boxes
- Free usable space below the device placement shelf
- Castor model: solid synthetic castors, 75 mm dia, 8 steering castors, 2 of which have brakes



Front cooking station

Illustration	Model	Designation	Dimensions W x D x H (mm)	Socket outlets/power/ connected load	Order No.	Price in € w/o VAT
	BC FS 2	Front cooking station with removable placement shelf Maximum load: approx. 150 kg	<u>Exterior dimensions:</u> 1538 x 750 x 1361 mm <u>Height of underframe:</u> 900 mm <u>Device placement niche:</u> 806 x 648 x 300 mm <u>Usable space below place- ment shelf:</u> 830 x 648 x 575 mm	2 x 230 V Schuko socket outlets, 2 x 400 V CEE socket outlets (max. 10 kW) 16 A CEE plug 400 V, 50/60 Hz, 3N PE, 10.8 kW	573 973	
	BC FS 3	Front cooking station with removable placement shelf Maximum load: approx. 150 kg	<u>Exterior dimensions:</u> 1943 x 750 x 1361 mm <u>Height of underframe:</u> 900 mm <u>Device placement niche:</u> 1211 x 648 x 300 mm <u>Usable space below placement shelf:</u> 1235 x 648 x 575 mm	3 x 230 V Schuko socket outlets, 3 x 400 V CEE socket outlets (max. 20 kW) 32 A CEE plug 400 V, 50/60 Hz, 3N PE, 20.8 kW	573 974	
	BC FS 3 BHG	Front cooking station with removable placement shelf, with lighting, closed sneeze guard and railing Maximum load: approx. 150 kg		3 x 230 V Schuko socket outlets, 3 x 400 V CEE socket outlets (max. 20 kW) 32 A CEE plug 400 V, 50/60 Hz, 3N PE, 20.8 kW	573 975	

BLANCO COOK front cooking station


- For 2, 3 or 4 BLANCO COOK table-top units
- Narrow extraction bridge for ideal visibility
- Extremely effective filter system
- Electronic control with filter change indicator
- Large storage surface on the odour filter boxes
- Free usable space below the device placement shelf
- Castor model: solid synthetic castors, 75 mm dia, 8 steering castors, 2 of which have brakes



Front cooking station





Illustration	Model	Designation	Dimensions W x D x H (mm)	Socket outlets/power/ connected load	Order No.	Price in € w/o VAT
	BC FS 4	Front cooking station with removable placement shelf and closed sneeze guard Maximum load: approx. 150 kg	<u>Exterior dimensions:</u> 2348 x 750 x 1361 mm <u>Height of underframe:</u> 900 mm <u>Device placement niche:</u> 1616 x 648 x 300 mm <u>Usable space below placement shelf:</u> 1640 x 648 x 575 mm	4 x 230 V Schuko socket outlets, 4 x 400 V CEE socket outlets (max. 20 kW) 32 A CEE plug 400 V, 50/60 Hz, 3N PE, 20.8 kW	573 976	

Connected loads, socket outlets

Illustration	Designation	For models	Order No.	Price in € w/o VAT
not shown	Connected load 16 A CEE plug, 400 V, 50/60 Hz, 3N PE, 10.8 kW	BC FS 3		
	32 A CEE plug, 400 V, 50/60 Hz, 3N PE, 20.8 kW	BC FS 2		
	63 A CEE plug, 400 V, 50/60 Hz, 3N PE, 40.8 kW	BC FS 4		
	Additional socket outlets 2 x 230 V Schuko socket outlets, in the usable space below the placement shelf, located both on the right and the left	all BC FS		


Accessories for front cooking station

Options for front cooking station BC FS

Illustration	Designation	For models	Order No.	Price in € w/o VAT
not shown	ION TEC electrostatic filtering for improved filtering and reduction of odour particles and blue smoke, increases the service life of the activated charcoal filters	all BC FS		
	Lighting with LED spots (4 W each) located above the cooking units	5 spots, 20 W		
		7 spots, 28 W		
		9 spots, 36 W		
	Sneeze guard made of safety glass (ESG) closed to customer side, can be folded up for cleaning	BC FS 2		
		BC FS 3		
		BC FS 4		
	Railing , made of stainless steel round tube, on the customer and short sides	BC FS 2		
		BC FS 3		
		BC FS 4		
not shown	Tray slide made of stainless steel round tube, on the customer side, can be folded down	Height 885 mm for castor dimension 75 mm, corresponds to the normal height of the BASIC LINE tray slide	BC FS 2	
			BC FS 3	
			BC FS 4	
		Height 850 mm for castor dimension 75 mm, corresponds to the height of the MANHATTAN tray slide	BC FS 2	
			BC FS 3	
			BC FS 4	

Accessories for front cooking station


Options for front cooking station BC FS

Illustration	Designation	For models	Order No.	Price in € w/o VAT
	Panelling made of HPL (High Pressure Laminate), colour: FunderMax 0077-FH, 0077-FH, material thickness: 4 mm, other colours available on request	on customer side	BC FS 2	
			BC FS 3	
			BC FS 4	
		on short side, on right or left	all BC FS	
not shown	Base bottom made of stainless steel, removable, maximum load: 80 kg		BC FS 2	
			BC FS 3	
			BC FS 4	
not shown	Stainless steel castors , 8 steering castors, 2 of which have brakes, 125 mm dia. , total height is increased by 60 mm, height of the underframe is then 960 mm		all BC FS	
not shown	Feet made of stainless steel		all BC FS	
not shown	Skirting panels made of stainless steel, on customer side		BC FS 2	
			BC FS 3	
			BC FS 4	

Accessories for BLANCO COOK



Underframe cooling table for BLANCO COOK BC FS 3, BC FS 4

Illustration	Model	Designation	Dimensions W x D x H (mm)	Power/ Connected load	Order No.	Price in € w/o VAT
	KTE 2-462	Underframe cooling table 2 hinged doors, 2 height-adjustable support ledges for Gastronorm containers (max. 2 x GN 1/1), for rolling into BC FS 3, BC FS 4	1190 x 654 x 564 mm	220 – 240 V 1N PE 16 A 50 Hz 0.265 kW	370 396	
		Instead of a door, two full extensions one on top of the other (usable height 135 mm)				
		GN grate GR 1/1, made of stainless steel			550 267	
		GN grate, Rilsan-coated, GRR 1/1			550 269	

Accessories

Illustration	Designation	For models	Order No.	Price in € w/o VAT
not shown	Transport dolly BC ROL 6x4 for rolling a BLANCOTHERM 420 into the free usable space, synthetic castors, 4 steering castors, 2 of which have brakes, 50 mm dia.	all BC FS	573 570	
	Multi-frame with bracket made of stainless steel for customer-side fastening to the odour filter boxes, for holding a GN 1/3 or its subdivision, including bracket for holding a roll of paper towels	all BC FS	573 977	
	Insert base made of glass for insertion into the multi-frame as additional storage surface	Multi-frame	573 978	
	Drawer insert set consisting of two rails for holding a GN 1/1, to be mounted on the underside of the unit placement shelf	all BC FS	573 979	
	BLANCO COOK system instruction technical instruction (cleaning, filter change) for the BLANCO COOK front cooking station installed ready for operation, handling the BLANCO COOK table-top units. Date upon request.	all BC FS	999 112	

BLANCO COOK table-top units



- Smooth Ceran surface
- Microprocessor-controlled high-performance induction generator made by E.G.O.
- Continuous power adjustment with rotary knob, indicator light to display operating mode and error code in the event of faults
- High efficiency
- Air filter on unit base
- Height-adjustable rotating feet, mains connection cable (1.5 m)



Induction hob

Illustration	Model	Designation	Dimensions L x W x H (mm)	Rating/ conn. load	Order No.	Price in € w/o VAT
	<u>BC IH 3500</u>	Induction hob, automatic pot detection from 120 mm dia.	Exterior dimensions: 620 x 400 x 240 mm Usable area: 564 x 339 mm Cooking zone: 220 x 220 mm Weight: 19 kg	220–240 V 1N PE 16 A 50–60 Hz 3.5 kW	574 197	
	<u>BC IH 5000</u>	Induction hob, automatic pot detection from 120 mm dia.	Exterior dimensions: 620 x 400 x 240 mm Usable area: 564 x 339 mm Cooking zone: 220 x 220 mm Weight: 19 kg	400 V 3N PE 16 A 50–60 Hz 5.0 kW	574 198	
	<u>BC IH 2Z 5000</u>	2-zone induction hob, 2 separately adjustable heating zones (2 coils, each with 220 mm dia.), automatic pot detection from 120 mm dia.	Exterior dimensions: 620 x 400 x 240 mm Usable area: 564 x 339 mm 2 cooking zones, each with Ø 220 mm Weight: 27 kg	400 V 3N PE 16 A 50–60 Hz 2 x 2.5 kW (5.0 kW)	574 199	
	<u>BC SIH 5000</u>	Surface induction hob, 1 rectangular cooking zone (1 heating zone 447 x 220 mm), automatic pot detection from 120 mm dia.	Exterior dimensions: 620 x 400 x 240 mm Usable area: 564 x 339 mm Cooking zone: 447 x 220 mm Weight: 27 kg	400 V 3N PE 16 A 50–60 Hz 5.0 kW (2 x 2.5 kW)	574 200	

Induction wok

	<u>BC IW 3500</u>	Induction wok	Exterior dimensions: 620 x 400 x 240 mm Cuvette: 300 mm dia. Weight: 18 kg	220–240 V 1N PE 16 A 50–60 Hz 3.5 kW	574 201	
	<u>BC IW 5000</u>	Induction wok	Exterior dimensions: 620 x 400 x 240 mm Cuvette: 300 mm dia. Weight: 18 kg	400 V 3N PE 16 A 50–60 Hz 5.0 kW	574 202	

The underlined models are available for delivery within 72 hours in commercially available volumes and standard packaging (subject to prior sale).

BLANCO COOK table-top units


- All-round seamlessly welded, 15 mm-thick griddle with rounded corners for optimal hygiene and even, full-surface heat distribution through tubular heating elements
- Unheated resting zone (70 mm) on operator side
- Continuous temperature adjustment with rotary knobs
- Indicator lights to display operating mode and heating phase
- Height-adjustable rotating feet, mains connection cable (1.5 m)



Griddle

Illustration	Model	Designation	Dimensions L x W x H (mm)	Rating/ conn. load	Order No.	Price in € w/o VAT
	<u>BC GF 3500</u>	Griddle, flat incl. grease drain plug, extremely powerful from +80 to +250 °C	Exterior dimensions: 620 x 400 x 240 mm Usable area: 506 x 304 mm of which 435 x 304 mm is heated Weight: 34 kg	220–240 V 1N PE 16 A 50–60 Hz 3.5 kW	574 203	
	<u>BC GF 4200</u>	Griddle, flat incl. grease drain plug, extremely powerful from +80 to +250 °C	Exterior dimensions: 620 x 400 x 240 mm Usable area: 506 x 304 mm of which 435 x 304 mm is heated Weight: 34 kg	400 V 3N PE 16 A 50–60 Hz 4.2 kW	574 204	
	<u>BC GF 8400</u>	Griddle, flat incl. grease drain plug, extremely powerful from +80 to +250 °C, 2 separately adjustable heating zones	Exterior dimensions: 620 x 800 x 240 mm Usable area: 506 x 704 mm of which 435 x 704 mm is heated Weight: 69 kg	400 V 3N PE 16 A 50–60 Hz 8.4 kW (2 x 4.2 kW per heating zone)	574 205	
	<u>BC GR 3500</u>	Griddle, ribbed incl. grease drain plug, extremely powerful from +80 to +250 °C	Exterior dimensions: 620 x 400 x 240 mm Usable area: 506 x 304 mm of which 435 x 304 mm is heated Weight: 31 kg	220–240 V 1N PE 16 A 50–60 Hz 3.5 kW	574 206	
	<u>BC GR 4200</u>	Griddle, ribbed incl. grease drain plug, extremely powerful from +80 to +250 °C	Exterior dimensions: 620 x 400 x 240 mm Usable area: 506 x 304 mm of which 435 x 304 mm is heated Weight: 31 kg	400 V 3N PE 16 A 50–60 Hz 4.2 kW	574 207	

Grill-Bräter


	<u>BC DG 4200</u>	Deep griddle incl. grease drain plug, extremely powerful from +80 to +250 °C	Exterior dimensions: 620 x 400 x 240 mm Usable area: 506 x 304 mm Capacity: 7 litres Basin depth: 65 mm Weight: 33 kg	400 V 3N PE 16 A 50–60 Hz 4.2 kW	574 208	
---	--------------------------	---	--	--	----------------	--

BLANCO COOK table-top units

- Continuous temperature adjustment with rotary knobs
- Height-adjustable rotating feet
- Mains connection cable (1.5 m)



Ceran® hob

Illustration	Model	Designation	Dimensions L x W x H (mm)	Rating/ conn. load	Order No.	Price in € w/o VAT
	BC CH 4300	Ceran® hob, indicator lights to display operating mode	Exterior dimensions: 620 x 400 x 240 mm Usable area: 564 x 339 mm Cooking zone: 170 mm dia. and 230 mm dia. Weight: 12 kg	400 V 3N PE 16 A 50–60 Hz 4.3 kW	574 209	

Pasta cooker




	BC PC 4800	Pasta cooker, seamlessly deep-drawn basin, for the insertion of GN containers or pasta baskets up to 150 mm in depth, indicator light to display operat- ing mode and heating phase	Exterior dimensions: 620 x 400 x 240 mm Usable area: 509 x 304 mm Capacity: 20 litres Weight: 14 kg	400 V 3N PE 16 A 50–60 Hz 4.8 kW	574 210	
	Pasta basket set Baskets with insulated handles and insertion frame		6 baskets: approx. GN 1/6-100		574 254	
	Pasta basket set Baskets with insulated handles and insertion frame		2 baskets: approx. GN 1/3-100 and 2 baskets: approx. GN 1/6-100		574 255	
	Gastronorm cooking insert G-KEN G 1/1-95 perforated, with folding handles		For additional GN cooking inserts, please turn to page 30		550 971	
	Lid with handle, GD 1/1 for covering				550 658	

BLANCO COOK table-top units


- Continuous temperature adjustment with rotary knobs
- Indicator lights to display operating mode and heating phase
- Height-adjustable rotating feet, mains connection cable (1.5 m)




Deep fryer

Illustration	Model	Designation	Dimensions L x W x H (mm)	Rating/ conn. load	Order No.	Price in € w/o VAT
 <p>BC DF 5000 (shown with accessories)</p>	BC DF 5000	Deep fryer Seamlessly deep-drawn basin, cold zone at the bottom of the basin, swivelling, interior heating elements, incl. lid to cover deep-frying basin	Exterior dimensions: 620 x 400 x 240 mm Usable area: 346 x 238 mm Capacity: min. 5 litres, max. 6.5 litres Weight: 16 kg	400 V 3N PE 16 A 50–60 Hz 5.0 kW	574 211	
		Deep-frying basket set (2 pcs.) with insulated handles	260 x 95 x 110 mm each		574 258	
		Deep-frying basket with insulated handle	260 x 220 x 110 mm		574 259	

Bain-marie

 <p>BC BM 700</p>	BC BM 700	Bain-marie Seamlessly deep-drawn basin, suitable for stainless-steel GN containers and GN lids, can be heated from +45 to +95 °C	Exterior dimensions: 620 x 400 x 240 mm Usable area: 509 x 304 mm Capacity: max. 1 x GN 1/1-150 Weight: 15.5 kg	220–240 V 1N PE 16 A 50–60 Hz 0.7 kW	574 212	
--	------------------	--	---	--	----------------	--

Hot plate


 <p>BC HP 700</p>	BC HP 700	Hot plate Hot plate with thermally separated heating-retaining area, silicone-sealed heat-retaining surface made of stainless steel, temperature range: +55 to +120 °C	Exterior dimensions: 620 x 400 x 240 mm Usable area: 565 x 340 mm Weight: 18 kg	220–240 V 1N PE 16 A 50–60 Hz 0.7 kW	574 213	
--	------------------	--	--	--	----------------	--

BLANCO COOK table-top units

- Height-adjustable rotating feet













Multi-element

Illustration	Model	Designation	Dimensions L x W x H (mm)	Rating/ conn. load	Order No.	Price in € w/o VAT
	BC ME	Multi-element	Exterior dimensions: 620 x 400 x 240 mm Capacity: Top: max. GN 1/1-150 (depending on depth of container located below) Below: max. GN 1/1-100 (in the case, top max. GN 1/1-65) Weight: 7 kg		573 458	

Accessories for BLANCO COOK table-top units

Accessories

Illustration	Designation	For model	Order No.	Price in € w/o VAT
	Ceran® cleaning scraper	For BC IH, induction hob, BC CH Ceran® hob	568 489	
	Round-bottom wok made of stainless steel, 360 mm dia., max. capacity 5.5 litres, weight 1.2 kg	For BC IW induction wok	573 513	
	Pasta basket set Baskets with insulated handles and insertion frame	6 baskets: approx. GN 1/6-100	574 254	
		2 baskets: approx. GN 1/3-100 and 2 baskets: approx. GN 1/6-100	574 255	
	G-KEN G 1/1-95 Gastronorm cooking insert perforated, with folding handles	For BC PC pasta cooker	550 971	
	Lid with handle, GD 1/1 for covering	For BC PC pasta cooker	550 658	
	Grill cleaning scraper, flat	For BC DG deep griddle, for BC GF griddle, flat	573 252	
not shown	Grill cleaning scraper, ribbed	For BC GR griddle, ribbed	574 306	
	Splash guard	For BC GF and BC GR griddles (except BC GF 8400)	574 256	
		For BC GF 8400 griddle	574 257	
not shown	BLANCO COOK anti-stick care 500 ml, protects and cares for the grill surface and improves anti-stick performance	For griddles and deep griddles	574 302	
	Deep-frying basket set (2 pcs.) with insulated handles 260 x 95 x 110 mm each (L x W x H)	For BC DF deep fryer	574 258	
	Deep-frying basket with insulated handles 260 x 220 x 110 mm each (L x W x H)	For BC DF deep fryer	574 259	
	Clamping bar made of stainless steel to cover the gap between two BLANCO COOK table-top units	For all models	574 298	

The underlined models are available for delivery within 72 hours in commercially available volumes and standard packaging (subject to prior sale).

